



US-Pro US-146 BT700

Patented Random Orbit Technology www-u-sand.com

2017

Page **1** of **10**



Unit	US-146	US-PRO	BT700
Weight	125	115	147
Motor	1.5HP	1.5HP	3HP
Power	110	110	220
Power Cord Length	25'	25'	50′

All units include-(4) four 6" backer pads, (1) one adjustable dust skirt, power cord, vacuum bag

These units are ready to run minutes out of the box. Choose your paper and you are ready to go!

INTERCHANGEABLE PARTS FOR ALL THREE INTERCHANGEABLE PARTS FOR ALL THREE UNITS **UNITS** BP6 US115-146 6" Backer Pad-foam pads that attach to the Dust Skirt-removable clear plastic backed hook and bottom of the unit using a ¾" open end wrench. loop skirt that is adjusted according the height of Allows the unit to float across the floor. the floor for optimum vacuum capabilities. BPS6 US114-146 6" Backer Pad Saver-thin material with hook Flanged grip for hand comfort when running the and loop on both sides to extend the hook and machine loop life of the backer pads. Sold as a pack of (4) US-VBAS14 **US-PORT** Fire Lock™ Va Tensioner assembled Vacuum adapter. Designed to fit snugly over the composed of fire retardant material. All warnings and blower exhaust outlet on the machine smaller end instructions are printed on the bag for safe use. is for attachment to a separate vacuum system. Used to collect the dust created when using the machine.

US115-146B

Dust skirt permanently attached to the base of the machine-The US115-146 removable dust skirt attaches to this for maximizing dust collection.



Lower Shaft Assembly

Consists of the lower shaft, 2 bearings and a snap ring to hold the bearings in place. The backer pads screw into this part of the spindle.





US-152

Gasket-sits between the motor and deck plate to ensure a snug dust free seal for the belt.



Serpentine belt used to drive the spindles enabling the backer pads to freely spin in a random orbit motion.





US119-146-Switch

Switch for sanders.

US119-146-Cover

Front and back of Switch Cover-Protects the switch from dust particles







MT-AS1

Fan blade with hub assembly bolted to the fan housing to pull dust from under the machine into the exhaust port



CH103-146

Fan housing-below the motor encases the MT-AS1 for dust extraction to the exhaust port



WRK-146P

Wheel replacement kit contains the following items 1 wheel, 2 washers, 1 wave spring, and 1 snap ring.



BT-AS

Belt tension assembly. Bolted on unit deck plate to keep belt tension steady and travel of the belt even between the spindles. Includes Belt tensioner, sleeve w/bearings, bolt and spring bolt.



HW-SP3/4 Spring for belt tensioner



Replace this spring when it no longer holds the tensioner tightly.



US-VBAS14-CLAMP

Clamp used to secure bag to hose



US-VBAS14-HOSE

Hose inserted into bag to fit over the vacuum port on machine for dust collection



PARTS FOR SPECIFIC UNITS

PC-146-FLP yellow cord

25' 110 power cord. Utilizing twist lock technology this cord is removable for easy transport and storage/replacement. Used on US-146/US-PRO—PC-146-FLPC grey cord



PARTS FOR SPECIFIC UNITS

PC-146-FLP-7

50' 220 power cord. Utilizing twist lock technology this cord is removable for easy transport and storage/replacement. Used on BT700 model



SP-AS

Spindle Assembly

Consists of a lower shaft assembly, main shaft, housing, bearings, spindle pulley and spacer. This part transfers the belt action to the backer pads.



SP-AS-C for Pro units, SP-AS-7 for BT700 units

US132-146

10# counter weight. Installed on US-146 and BT700 units for added weight.



Not available for US-Pro units

TOOLS USED FOR ALL THREE UNITS

TOOLS USED FOR ALL THREE UNITS

SK-020611-01

Spanner Wrench

This wrench is used to loosen the spindle housing nut to release the spindle from the deck plate(sometimes a chisel is needed to crack this loose, a new nut is sent with each rebuilt spindle)



SH-146

Slide Hammer

This tool is used to remove the lower shaft from the spindles when the bearings need replaced. It inserts via the same way the backer pads connect. Then you work the tool to pull the lower shaft from the spindle



US142-146

Knob for handle unit-adjustor for upper handle



WH-AS1

Wheel assembly sub-axle and bracket, attaches to the deck plate.



A-102060-19 or A-102060-3 3HP 1.5HP

3HP or 1.5HP run capacitors for motors.



A-A35406-2385 or A-A35406-44U 3HP 1.5 HP

3HP or 1.5HP start capacitors for motors.



F-146 FC-146,or FC-PRO, or FC-700 Replacement motor fan (plastic). This is on top Replacement motor fan cover this encases the of the motor under the cover. plastic fan on the left. Specify motor when ordering **HW-Manual Reset Switch Cover HW-Manual Reset** Replacement manual reset switch for Pro and Manual reset switch cover for Pro and BT700 units only. Bt700 units only PC-146-MLP – US-146 unit PC-146B - US-146 unit 43" Cord from switch to motor 17" Cord from switch to extension cord PC-146-MLPC- grey PRO UNIT PC-146C - PRO UNIT PC-146B-7 BT700 UNIT PC-146S-7 - yellow BT700 UNIT

UP-HANDLE

Upper handle unit powder coated includes electric box. Must specify color-beige, silver, yellow.




LO-HANDLE

Lower handle unit powder coated. Must specify color- beige, silver, yellow



CH102-146

Belt Cover unit-(2pc set) front and backspecify unit



CH102-146-beige,

CH102-146-P Black CH102-146-7 yellow



Base Plate-must specify color



CH102-146-beige, CH102-146-C silver, CH102-146-7 yellow



Hint: always make sure belt is running level from one spindle to the next after replacing belt. Adjust height by moving the tensioner up/down with a bar to adjust belt to run straight from one spindle to the next.

For maintenance and repair instructions please visit our website and view detailed instructions.

http://www.u-sand.com/rentalcustomers/manuals.aspx

or

www.u-sand.com

customer help download operations manual you will find the maintenance manuals available for all units

ABRASIVES	ABRASIVES
U-600K	
6" Buff Pads a maroon colored pliable but rough material used to remove build up on floors that need a light buff and new coat of	For best performance use paper recommended by the manufacturer of the equipment you are using.
finish. Also used as a gentle abrasive for scuffing the first coat of finish to ensure good adhesion of the latter layers of finish. Sold in a (4) pack.	Paper recommended by us has been tested to perform well on our equipment.

Sandpaper Packaging Options

Available in standard 20discs pkg.
Or 60-disc Contractor Box (CP) packaging

Aluminum Oxide (S)

Grits-24,36,40,60,80,100,120,180,220

- Sturdy D-paper, high tear resistance, Resin over resin, very open coat,
- New Flooring/old Floor Refinishing
- Optimized price performance ratio easy to use

Premium Zirconia (Z)

Grits-24,36,40,60,80,100,120

- . Extra heavy cloth backing extends the life of these discs
- New Flooring/old Floor Refinishing
- Self –sharpening abrasive for long service life
- Extremely high abrasive performance